

10/537768

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



537768

(43) International Publication Date
24 June 2004 (24.06.2004)

PCT

(10) International Publication Number
WO 2004/053478 A1

(51) International Patent Classification⁷:
30/86

G01N 30/32,

(74) Agent: MARIETTI, Andrea,; Marietti, Gislon e Trupiano S.r.l., Via Larga, 16, I-20122 Milan (IT).

(21) International Application Number:

PCT/IB2003/005706

(22) International Filing Date: 5 December 2003 (05.12.2003)

(25) Filing Language: Italian

(26) Publication Language: English

(30) Priority Data:

MI2002A 002605 9 December 2002 (09.12.2002) IT

(71) Applicant (for all designated States except US):
THERMO FINNIGAN ITALIA S.p.A. [IT/TT]; Strada
Rivoltana, I-20090 Rodano (IT).

(72) Inventor; and


(75) Inventor/Applicant (for US only): MAGNI, Paolo
[IT/TT]; Viale Lombardia, 1, I-26010 Izano (IT).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: A METHOD AND APPARATUS FOR KEEPING CONSTANT THE RETENTION TIMES IN A GASCHROMATOGRAPHIC ANALYSIS



(57) Abstract: A method for obtaining reproducibility of the retention times of the components of a mixture to be analysed in an apparatus for gaschromatographic analysis provided with a capillary column, when there occurs one of the following variations: variation in the length of the column, or alternatively its replacement with a column having identical real specifications with the exception of the length, and/or variation in the pressure of the carrier gas at output from said column. The method envisages that the pneumatic resistance of the column is known and preferably measured before and after the aforesaid variations, and that a new input pressure or a new mass flow of the carrier gas will be entered into said apparatus for gaschromatographic analysis in relation to said values of pneumatic resistance.

WO 2004/053478 A1



Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.